

# Interface® | Heuga 727 SD

## SPECIFICATION

<b>Product definition</b>	Tufted Level Loop Pile	<b>Style number</b>	<b>607277</b>
<b>Pile Material</b>	100% Nylon	<b>Wear Classification</b>	EN 1307 33 Heavy Contract
<b>Pile Yarn Weight</b>	535 g/m <sup>2</sup> ± 10%	<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
<b>Effective pile yarn weight</b>	310 g/m <sup>2</sup> ± 10%	<b>Hot Metal Nut Castor Chair Rating</b>	≥ 2,4 (EN 985)
<b>Total Weight</b>	4240 g/m <sup>2</sup> ± 5%	<b>Dimensional Stability</b>	≤ 0,2% (ISO 2551 / EN 986)
<b>Pile Height</b>	2.3 mm ± 0.5 mm	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω >< 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965)
<b>Total Thickness</b>	6.1 mm ± 0.5 mm	<b>Colour Fastness - Light</b>	≥ 7 (ISO 105/B02)
<b>Gauge/Ends per 10cm</b>	1/10 - 39.4	<b>Tiles per Box</b>	20 - (50 x 50 cm ± 0,2%)
<b>Tufts per m<sup>2</sup></b>	157600 ± 7.5%		
<b>Backing Type</b>	Graphlex®		

**CE**  
06  
0336-CPD-8538

Cfl-s1

DS

≤10<sup>9</sup>Ω

≤10<sup>9</sup>Ω

EN 1307

Monolithic

Quarter Turn

GUT

BCDFBD76

23 dB

Performance Profile: Solarex  
Certificate Number: ENP-407



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

[www.interface.com](http://www.interface.com)